

D E S C R I P T I O NPRODUCT COVERED:

USR, CNR: Component - Special-Use Switches

<u>Cat. No.</u>	<u>Elec. Rating</u> <u>A-V-F-HP</u>	<u>Temp.,</u> <u>Deg. C</u>	<u>POL/</u> <u>THR</u>	<u>PP</u>	<u>ENDUR</u>	<u>SPCOA</u>
R13-104, f/b *A, B or C	10 A, 125V/250 V ac, 60 Hz	55 2/2	2/1, 1/1	PP	6K	2
R13-105, f/b A, B or C	10 A, 125V/250 V ac, 60 Hz	55 2/2	2/1,	PP	6K	2
R13-117, f/b A, B or C	10 A, 125V/250 V ac, 60 Hz	55 2/2	2/1,	PP	6K	-
R13-120, f/b A or B	10 A, 125V/250 V ac, 60 Hz	55	1/1	--	6K	2
R13-121, f/b A or B	10 A, 125V/250 V ac, 60 Hz	55	1/1	--	6K	2

EXPLANATION OF PRODUCT COVERED TABLE:

Abbreviations f/b - followed by
if used ww/o- with or without

POL/THR - No. of Poles/No. of Throws.

PP - "PP" stands for Per Pole. PP in this column indicates that each pole is capable of switching the rated current.

ENDUR - Endurance Rating

SPCOA - Special Conditions of Acceptability; the applicable special COAs are indicated in this column in number form. The corresponding COAs are given in the following pages.

HN/CN:ac1
SCDLS