

# **MSDS Report**



Client un	it:	SHENZHEN PKCELL BATTERY CO.,LTD				
Name of	sample:	Alkaline B	utton Battery	,		
Address:	and the second se		0, 0	g Technology ua New Area,		
Tested by:	Xielingling (	Checked Dy:	Calmi .	Approved By:	Billow	
Date:	Jan.07, 2015	Date:	Jan.07, 2015	Date:	Jan.07, 2015	

CCIC Southern Electronic Product Testing (Shenzhen) CO., Ltd. **查询码:BK2DS0SC** Add: Building 28/29, Shigudong, Xili Industrial Area, Xili Street, Nanshan District, Shenzhen, Guangdong, China (pc: 518055) <u>http://www.ccic-set.com</u> Tel: 0755-86913585, 26701907 Fax: 0755-26701436



# **1 Identification of substance**

**Product details** 

Product name: Alkaline Button Battery

Manufacturer: SHENZHEN PKCELL BATTERY CO., LTD

Address: E2 Building, Guangming Technology Park, No.24 Zhonghua Road, Longhua New Area, Shenzhen, China

Producer: SHENZHEN PKCELL BATTERY CO.,LTD

Address: E2 Building, Guangming Technology Park, No.24 Zhonghua Road, Longhua New Area, Shenzhen, China

Model No.: AG0 / AG1 AG2 / AG3 / AG4 / AG5 / AG6 / AG7 / AG8 / AG9 / AG10 / AG11 / AG12/ AG13 / LR1130 / LR44 / LR41 / 23A / 27A /LR521 /LR621/ LR726 /LR626/ LR754/ LR921/ LR927/ LR1120 / LR45 /LR721/ LR43

rel: 0755-86670642 Eme

Emergency telephone: 0755-86670643

Fax: 0755-86670609

Mail: info@pkcell.com

**MSDS Code:** SET2014-14782

#### 2 Composition/Data on components

Chemical characterization: Description : (CAS#)

Chemical Name	In % By Weight	CAS No.	EC No.	Molecular Formula			
Manganese Dioxide	38.5	1313-13-9	215-202-6	MnO <sub>2</sub>			
Zinc	21.0	7440-66-6	231-175-3	Zn			
Graphite	3.0	7782-42-5	231-955-3	С			
Potassium Hydroxide (liquid)	9.5	1310-58-3	215-181-3	КОН			
Copper	1.0	7440-50-8	231-159-6	Cu			
Iron	14.0	7439-89-6	231-096-4	Fe			
Water	10.5	7732-18-5	231-791-2	H <sub>2</sub> O			
Nylon	2.5	74937-16-4	NA	NA			

Abbreviation: CAS No. is Chemical Abstract Service Registry Number. EC No. is European Inventory of Existing Commercial chemical Substances Number. NA = Not apply.

# **3 Hazards identification**

**Emergency Overview:** May explode in a fire, which could release hydrogen fluoride gas. Use extinguishing media suitable for materials burning in fire.

CCIC Southern Electronic Product Testing (Shenzhen) CO., Ltd.

Add: Building 28/29, Shigudong, Xili Industrial Area, Xili Street, Nanshan District, Shenzhen, Guangdong, China (pc: 518055) <u>http://www.ccic-set.com</u> Tel: 0755-86913585, 26701907 Fax: 0755-26701436





# Material Safety Data Sheet

Page: 3 of 6 **No.SET2014-14782** Reviewed on Jan.07, 2015

# **Primary routes of entry:** Skin contact, Eye contact, Inhalation, Ingestion **Symptoms of exposure:**

Skin contact: Contact with damaged batteries may cause burns.

Eye contact: Contact with damaged batteries may cause burns. Eye damage is possible.

Inhalation: Inhalation of vapors or fumes released due to heat or a large number of leaking batteries may cause respiratory and eye irritation.

Ingestion: Swallowing is not anticipated due to battery size. Ingestion of battery contents may cause mouth, throat and intestinal burns and damage.

Reported as carcinogen: Not applicable.



# 4 First aid measures

Analation Not a health hazard. A ye contact Not a health hazard. Skin contact Not a health hazard. Ingestion

If swallowed, obtain medical attention immediately.

# IF EXPOSURE TO INTERNAL MATERIALS WITHIN CELL DUE TO DAMAGED OUTER CASING, THE FOLLOWING ACTIONS ARE RECOMMENDED;

Inhalation

Leave area immediately and seek medical attention.

Eye contact

Rinse eyes with water for 15min.

Skin contact

Wash area thoroughly whit soap and water and seek medical attention.

#### Ingestion

Drink milk/water and induce vomiting; seek medical attention.

# **5** Fire fighting measures

#### General Hazard:

Cell is not flammable. Combustion products include, but are not limited to Hydrogen fluoride, carbon monoxide and carbon dioxide.

#### **Extinguishing Media:**

Use extinguishing media suitable for the materials that are burning.

# **Special Fire fighting Instructions:**

If possible, remove cell(s) from fire fighting area, If heated above 160°C, cell(s) may explode/vent.

# Fire fighting Equipment:

Use NIOSH/MSHA approved full-face self-contained breathing apparatus (SCBA) with full protective gear.

CCIC Southern Electronic Product Testing (Shenzhen) CO., Ltd.

Add: Building 28/29, Shigudong, Xili Industrial Area, Xili Street, Nanshan District, Shenzhen, Guangdong, China (pc: 518055) <u>http://www.ccic-set.com</u> Tel: 0755-86913585, 26701907 Fax: 0755-26701436





# 6 Accidental release measures

On land:

Place material into suitable containers and call local fire/police department. **In water:** 

If possible, remove from water and call local fire/police department.

# 7 Handling and storage

**Handling:** Closed operation. To supply with sufficient partial air exhaust. The operating staff must have received special training and abide by the operating regulations. It is advised that the staff wear work clothes, respirator, chemical protective glasses and gloves. Keep away from fire and heating sources. No moking in the workplace. Avoid contacting with oxidizers and acid. Do not expose the battery to excessive physical shock or vibration. Short-circuiting should be avoided. Place the cell beyond the child's reach. Take care when transport, prevent damaging the packing and container. Equip with relevant types and quantities of extinguishment instruments and device for divulgence handling. Empty the container which may include harmful material.

**Storage:** Store in a cool, dry place. Keep away from fire and heating sources. Don't keep the samples with oxidizer and acid. Equip with relevant types and quantities of the extinguishment instruments. The storage place should be equipped with suitable shelter materials for divulgence handling.

# 8 Exposure controls and personal protection

**Engineering controls:** Keep away from heat and open flame. Store in a cool dry place. **Personal Protection:** 

Respirator: Not required during normal operations. SCBA required in the event of a fire. Eye/face protection: Not required safety practices of employer.

Gloves: Not required for handling of cells.

Foot protection: Steel toed shoes recommended for large container handling.

# 9 Physical and chemical properties:

**General Information** 

State: Button or cylindrical shape Color: Silvery Chemical properties: Melting Point: Not Applicable Vapor Pressure: Not Applicable Vapor Density: Not Applicable Solubility In Water: Insoluble Specific Gravity ( $H_2O = 1$ ): Not Applicable pH: Not Applicable Density: Not Applicable

CCIC Southern Electronic Product Testing (Shenzhen) CO., Ltd.

Add: Building 28/29, Shigudong, Xili Industrial Area, Xili Street, Nanshan District, Shenzhen, Guangdong, China (pc: 518055) http://www.ccic-set.com Tel: 0755-86913585, 26701907 Fax: 0755-26701436



## **10 Stability and reactivity**

Reactivity: None.

**Incompatibilities:** None during normal operation. Avoid exposure to heat, open flame, and corrosives. **Hazardous Decomposition Products:** None during normal operating conditions. If cells are opened, hydrogen fluoride and carbon monoxide may be released.

Conditions to Avoid: Avoid exposure to heat and open flame. Do not puncture, crush or incinerate.

**11 Toxicological information** 

SET

This product does not elicit toxicological properties during routine handling and use
Sensitization: The liquid in the battery may cause sensitization to some person.
Feratogenicity: No information is available.
Feproductive toxicity: No information is available.
Acute toxicity: No information is available.

If the cells are opened through misuse or damage, discard immediately. Internal components of cell are irritants and sensitizers.

### **12 Ecological information**

Some materials within the cell are bio-accumulative. Under normal conditions, These materials are contained and pose no risk to persons or the surrounding environment.

# **13 Disposal considerations**

California regulated debris RCRA Waste Code: Non-regulated Dispose of according to all federal, state, and local regulations.

#### **14 Transport information**

In general, all batteries in all forms of transportation (by sea, land or air) must be packaged in a safe and responsible manner. Regulatory concerns from all agencies for safe packaging require that batteries be packaged in a manner that prevents short circuits and be contained in "strong outer packaging" that prevents spillage of contents. All original packaging for energizer alkaline batteries has been designed to be compliant with these regulatory concerns.

Alkaline batteries are not classified as dangerous goods under the IATA Dangers Good Regulations, with complying to the Special Provision A123, and all applicable carrier and government regulations.

Examine whether the package of the containers are integrate and tighten closed before transport. No divulgence, no collapse, no precipitation or no damage during the course of transportation. Don't put the goods together with oxidizer, acid. The transport vehicle and ship must be cleaned and sterilized otherwise

CCIC Southern Electronic Product Testing (Shenzhen) CO., Ltd.

Add: Building 28/29, Shigudong, Xili Industrial Area, Xili Street, Nanshan District, Shenzhen, Guangdong, China (pc: 518055) http://www.ccic-set.com Tel: 0755-86913585, 26701907 Fax: 0755-26701436



it is not allowed to assemble articles. During transport, the vehicle should prevent exposure, rain and high temperature.

# **15 Regulations**

OSHA Hazard communication standard (29 CFR 1910.1200) Hazardous \_\_\_\_\_ Non-hazardous √\_\_\_\_ ISO 11014-2009 Safety data sheet for chemical products - Content and order of sections. The International Air Transport Association (IATA) Dangerous Goods Regulations, 56<sup>th</sup>, 2015.



## 6 Other information:

The above information are correct, but does not contain all of the information and only used as a guide. The information in this document is based on our current knowledge, it apply to this product as for the correct safety tips. The information does not guarantee the properties of this product. Our company is not responsible for any damages caused by the products.

Note: -The model for test is LR44. -Sample photo:





CCIC Southern Electronic Product Testing (Shenzhen) CO., Ltd. Add: Building 28/29, Shigudong, Xili Industrial Area, Xili Street, Nanshan District, Shenzhen, Guangdong, China (pc: 518055) <u>http://www.ccic-set.com</u> Tel: 0755-86913585, 26701907 Fax: 0755-26701436