

# CERTIFICATE

Issued to:  
Applicant:  
**Foshan Shunde Ojun Electrical Co., Ltd.**  
**ChengZiLi Industrial Area, HongQi Zhong Road**  
**RongGui Avenue, Shunde Area**  
**FOSHAN CITY, GUANGDONG, China**

Manufacturer/Licensee:  
**Foshan Shunde Ojun Electrical Co., Ltd.**  
**ChengZiLi Industrial Area, HongQi Zhong Road**  
**RongGui Avenue, Shunde Area**  
**FOSHAN CITY, GUANGDONG, China**

Product : flexible cord switches  
Trade name : OJUN  
Type/model : 8s.317

The product and any acceptable variation thereto is specified in the Annex to this certificate and the documents therein referred to.

DEKRA hereby declares that the above-mentioned product has been certified on the basis of:

- a type test according to the standard EN 61058-1:2002 + A2:2008; EN 61058-2-1:2011
- an inspection of the production location according to CENELEC Operational Document CIG 021
- a certification agreement with the number 2100620

DEKRA hereby grants the right to use the ENEC KEMA-KEUR certification mark.

The ENEC KEMA-KEUR certification mark may be applied to the product as specified in this certificate for the duration of the ENEC KEMA-KEUR certification agreement and under the conditions of the ENEC KEMA-KEUR certification agreement.

This certificate is issued on: 8 January 2014 and expires upon withdrawal of one of the above mentioned standards.

Certificate number: 2168733.01

DEKRA Certification B.V.



drs. G.J. Zoetbrood  
Managing Director



H.R.M. Barends  
Certification Manager

© Integral publication of this certificate is allowed

ACCREDITED BY THE  
DUTCH ACCREDITATION  
COUNCIL



**SPECIFICATION OF THE CERTIFIED PRODUCT****Product data**

product	: flexible cord switches
trade name	: OJUN
type	: 8s.317
type reference	: common type (C.T.)
method of actuating	: push-button
rated current	: 2 ⊗ 2 A
rated voltage	: 250 V~
pattern no.	: 1
circuit to be controlled	: resistive and tungsten filament lamp
temperature limit	: T55
contact opening	: full disconnection
frequency of operation	: 10.000 operating cycles
class	: for class II appliances
degree of protection	: IP20
degree of pollution	: 2
insulating material	: tracking resistant 175 V
category to heat and fire	: 850°C
rated impulse withstand voltage	: 2500 V
material group	: IIIa
design	: non-rewirable
termination	: soldered connection
applied flexible cord	: H03VVH2-F 2x0,75 mm²
certification mark	: KEMA-KEUR / VDE
description	: body and actuating member of thermoplastic material
markings	: printed on the body

**TESTS****Test requirements**

EN 61058-1:2002 + A2:2008

EN 61058-2-1:2011

**Test result**

The test results are laid down in DEKRA test file 2168733.01.


**Remarks**

This certificate replaces our certificate 2143481.03 dated 3 March, 2011 and is also partly based on the results of that certificate.

**Conclusion**

The examination proved that all test requirements were met.

Tested by : J. He  
Checked by : J.C. Hendriksen

**Factory location**

Foshan Shunde Ojun Electrical Co., Ltd.  
ChengZiLi Industrial Area, HongQi Zhong Road  
RongGui Avenue, Shunde Area  
FOSHAN CITY, GUANGDONG, China