

**WOYR8.E236875****Switches, Appliance and Special Use Certified for Canada - Component**

For enhanced search functionality, please visit UL's [iQ™ Family of Databases](#).

Click on a product designation for complete information.

[Page Bottom](#)

Switches, Appliance and Special Use Certified for Canada - Component

[See General Information for Switches, Appliance and Special Use Certified for Canada - Component](#)

ZHE JIANG BEI ER JIA ELECTRONIC CO LTD

E236875

SONGHU INDUSTRIAL ZONE


7 SONGHU RD

YUEQING, ZHEJIANG 325600 CHINA

Investigated to CAN/CSA-C22.2 No. 61058-1

Cat. No.	Load	Amps	Volts	Hz	Temp (°C)	Pol/	Endurance		IP	Dis (mm)	SPCA	Std. Ed.
						Thr/ Cir	30C cycle	55C cycle				
Micro												
KW01, f/b D, A, M or H, f/b any number or letter, f/b A, may be f/b any number or letter, f/b 4 or 6, f/b any number or letter, f/b any number or letter, f/b any number or letter, f/b - any number or letter												
	RM	16(4)	250	50-60	125	1/2-3.3	6K	50K	00	micro	Note A	3
KW01, f/b D, A, M or H, f/b any number or letter, f/b B or C, may be f/b any number or letter, f/b 4 or 6, f/b any number or letter, f/b any number or letter, f/b any number or letter, f/b - any number or letter												
	RM	16(4)	250	50-60	125	1/1-1.2	6K	50K	00	micro	Note A	3
KW02 Series	R	0-16	125	50-60	40T125	1/1.2-1.2,3.3	6K	10K	40	micro	1A ,1B	2013-02-15
	R	0-16	125	50-60	40T125	1/1.2-1.2,3.3	6K	10K	55			
	R	0-16	125	50-60	40T125	1/1.2-1.2,3.3	6K	10K	67			
	RM	0-10.1(6)	250	50-60	40T125	1/1.2-1.2,3.3	6K	10K	40			
	RM	0-10.1(6)	250	50-60	40T125	1/1.2-1.2,3.3	6K	10K	55			
	RM	0-10.1(6)	250	50-60	40T125	1/1.2-1.2,3.3	6K	10K	67			
	hp	1/3	250	50-60	40T125	1/1.2-1.2,3.3	6K	10K	40			
	hp	1/3	250	50-60	40T125	1/1.2-1.2,3.3	6K	10K	55			
	hp	1/3	250	50-60	40T125	1/1.2-1.2,3.3	6K	10K	67			
	hp	1/6	125	50-60	40T125	1/1.2-1.2,3.3	6K	10K	40			
	hp	1/6	125	50-60	40T125	1/1.2-1.2,3.3	6K	10K	55			

	hp	1/6	125	50-60	40T125	1/1.2-1.2,3.3	6K	10K	67			
	R	0-5	0-48	DC	40T125	1/1.2-1.2,3.3	6K	50K	40			
	R	0-5	0-48	DC	40T125	1/1.2-1.2,3.3	6K	50K	55			
	R	0-5	0-48	DC	40T125	1/1.2-1.2,3.3	6K	50K	67			
	RM	0-5(3)	125-250	50-60	40T125	1/1.2-1.2,3.3	6K	50K	40			
	RM	0-5(3)	125-250	50-60	40T125	1/1.2-1.2,3.3	6K	50K	55			
	RM	0-5(3)	125-250	50-60	40T125	1/1.2-1.2,3.3	6K	50K	67			
Rocker												
PS8A, f/b 2,3,7,9,13 or 14, f/b any Letter(s), Number(s) or Blank, f/b 1,2,3,4,5 or 7, f/b H,S,C or K.												
	RM	12(6)	125-250	50-60	25T125/55	1,2/1,2-1.2,2.8	6K	50K	40	full 3.12	3A,3B	2009-08-10
	RM	8(6)	125-250	50-60	25T125/55	1,2/1,2-1.2,2.8	6K	50K	40			
	RM	4(4)	125-250	50-60	25T125/55	1,2/1,2-1.2,2.8	6K	50K	40			
	R	16	125	50-60	25T125/55	1,2/1,2-1.2,2.8	6K	10K	40			
PS8C, f/b 5,6 or 12, f/b any Letter(s), Number(s) or Blank, f/b L or Blank, f/b 1,2,5,7,8,9,10 or 11, f/b H,S,C or K.												
	RM	20(8)	125-250	50-60	25T125/55	1,2/1,2-2.8,3.8	6K	50K	40	full 3.12	3A,3B	2009-08-10
Slide												
PS10; f/b -1 or -2, f/b 2, 3 or 4, f/b A, B, C or D, f/b L, N or Blank, f/b 01, 02 or Blank.												
	RM	12(2)	125-250	50-60	25T105	1,2/M-1.2,1.4	6K	10K	20	full 3.4	2A,2B,2C	2009-08-10
	R	12	125-250	50-60	25T105	1,2/M-1.2,1.4	6K	10K	20			
	R	6	125-250	50-60	25T105	1,2/M-1.2,1.4	6K	10K	20			
PS8A, f/b 1,4,8 or 11, f/b any Letter(s), Number(s) or Blank, f/b 1,5 or 6, f/b H,S,C or K.												
	RM	12(6)	125-250	50-60	25T125/55	1,2/1-1.4/1.5	6K	50K	40	full 2.3	3A,3B	2009-08-10
	RM	8(6)	125-250	50-60	25T125/55	1,2/1-1.4/1.5	6K	50K	40			
	RM	4(4)	125-250	50-60	25T125/55	1,2/1-1.4/1.5	6K	50K	40			
	TV	5	125	50-60	25T125/55	1,2/1-1.4/1.5	6K	25K	40			

Marking: Company name or tradename "BEJ" or trademark  , catalog, model or part number, electrical ratings

and the Recognized Component Mark for Canada,  on the product or on the smallest unit container in which the product is packaged.

Investigated to CSA-C22.2 No. 55

Cat. No.	Amps	Volts	Hz	Load	Endurance	Temp C	POL/THR	Per Pole/Circuit Code	SPCOA
PS10	12	250	60	GP	-	85	2/2	-/-	A1,A2
	12	125	60	GP	-				
PS5	5	120	60	TV	25K	85	1/1	-/-	-
PS8A Series	10	125	50/60	GP	6K	85	1/1	-/A	-
	8	250	50/60	GP	6K				
	-	250	50/60	1/2hp	6K				
	-	125-250	50/60	1/4hp	6K				
PS8C	20	125	60	GP	6K	85	1/1	-/-	3
	16	125	60	GP	6K				
	16	250	60	GP	6K				
	-	250	60	3/4hp	6K				
	-	125	60	1/4hp	6K				
	-	250	60	1/4hp	6K				

1A - 1A. The Switch body is installed inside of end product; consider for no accessible parts. When mounted in accordance with the manufactures instruction, this switch gets a protection degree of IP 40/55/67

1B - The switch is to be employed in an end use product providing an enclosure or insulating barrier that provides Reinforced or Double Insulation over the front and rear switch enclosure Surfaces

2A - When mounted in accordance with the manufactures instruction, this switch gets a protection degree of IP 20.

2B - The switch is to be employed in an end use product providing an enclosure or insulating barrier that provides Reinforced or Double Insulation over the front and rear switch enclosure Surfaces.

2C - The switch is considered for without any accessible parts to the user.

3A - The Switch body is installed inside of end product; consider the Button for accessible parts. When mounted in accordance with the manufactures instruction, this switch gets a protection degree of IP 40.

3B - The switch is to be employed in an end use product providing an enclosure or insulating barrier that provides Reinforced or Double Insulation over the front and rear switch enclosure Surfaces.

A - The tabs of Series KW01 are only evaluated for connection via hand soldering by a soldering iron at 350 C with 1.5 mm2 stranded conductors, and solder bath at 235 C.

A1 - It is a voltage selector switch. The investigation was limited to Mechanical cycles and current conducting capability. This switch should not be used to Make or Break any load and are not to be evaluated for Make and Break capabilities in the end product.

A2 - The switch has been subjected to a minimum 6,050 cycles Mechanical Endurance Test with no load in lieu of the normal Overload/Endurance test. This Switch should not be operated under load in the end-product

Note A - UL61058-1 - The tabs of Series KW01 are only evaluated for connection via hand soldering by a soldering iron at 350 C with 1.5 mm2 stranded conductors, and solder bath at 235 C.

Marking: Company name or tradename "BEJ" or trademark  , catalog, model or part number, electrical ratings

and the Recognized Component Mark for Canada,  on the product or on the smallest unit container in which the product is packaged.

Last Updated on 2016-12-15

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

◆ 2016 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2016 UL LLC".