


**FUSEHOLDER BLOCKS FOR P.C.B.  
PORTAFUSIBILI NON PROTETTI PER C.S.**

**PTF/75**




Fuse link / Fusibile tipo	5x20 mm
Mounting / Montaggio	P.C.B. / C.S.
Rated Current / Corrente nominale	6,3 A
Rated Voltage / Tensione nominale	250 VAC
Rated Power Acceptance / Potenza dissipabile	1,6 W

Housing / Corpo isolante	Thermoplastic UL 94 V0
Admissible ambient air temperature / Temperatura ambiente ammissibile	-30 °C to 85 °C
Shocksafe category / Protezione contro le scosse elettriche	PC1
Degree of protection / Grado di protezione	IP00
Contact Resistance / Resistenza di contatto	< 5 mΩ

 EN 60127-6

Rated Current / Corrente Nominale	6,3 A	Rated Current / Corrente Nominale	20 A
Rated Voltage / Tensione nominale	250 VAC	Rated Voltage / Tensione nominale	250 VAC
Rated Power Acceptance / Potenza dissipabile	1,6 W	Rated Power Acceptance / Potenza dissipabile	—

 UL 4248-1 + C22.2 no. 4248-1

Standard colour / Colore standard	Green / Verde
Other colours / Altri colori	On demand / A richiesta
Accessories / Accessori	Cover / Cappuccio BS232 p. 36
Other information / Altri dati	p. 39
Standard package / Imballo	Bulk / Scatola 1000 pcs

