




COVER



**Specification:**

- Material:**  
 1. JACK Housing :PC/ABS,WHITE  
 2. RJ45 contact material & finished:  
 2-1.Phosphor Bronze with Nickel plated.  
 2-2.Contact area :Gold plated.

- 3.IDC Housing: PC  
 4.IDC Terminal material & finished:  
 4-1.Phosphor Bronze with Tin plated.  
 4-2. 110 tool compatible.  
 4-3. Suitable for 22-26 AWG stranded and solid wire.

**Performance:**

- a.The sticker color codes combine two wirings of T568A & T568B.  
 b.Insertion Force: 900 gms for 8 contacts.  
 c.Retention Strength: 7.7 kgs between Jack and Plug.  
 d.Operation Temperature: -20° to 68°.

**e.Durability:**

- e-1. Jack : 750 cycles Plug-Jack mating and unmating test, Insertion cycles at 20 cycles/minute max. Contact resistance test per 100 cycles.  
 e-2. IDC : Max. 200 punching times.

f.The Cat.5e performance is in compliance with the ANSI/TIA/EIA 568 C standard.

			Tolerance: .X ±0.5 .X ±0.3 .XX ±0.10	SCALE: FREE	CUSTOMER :			Approved by
			Angle: X° ±3° .X° ±1°	UNIT: mm	CUSTOMER P/N:		COMPANY P/N: 01.075.0078	Checked by
REV.	DESCRIPTION	DATE	REV. : OO		DWG. No. :		TITLE: UTP CAT5 KEYSTONE JACK,180°	Design by <b>XJH</b>