

NO	PART NO.	PLATING	MATERIAL
1	10110188D035	Au15u'	PC CLEAR UL94V-2
2	10110188A153	AuG/F	PC CLEAR UL94V-2
3	10110188A150	AuG/F-H	PC CLEAR UL94V-2

REV. 版本	ECN NO. 变更说明	DATE 日期
01		2012. 11. 19

SALT SPRAY	
G/F	NA
3u" 6u"	24H
15u" 30u"	48H
50u"	

SPECIFICATION NOTES:

1. ELECTRICAL:

- 1.1 VOLTAGE RATING: 150 VAC RMS
- 1.2 CURRENT RATING: 1.5 AMP
- 1.3 CONTACT RESISTANCE: 20mΩ MAX.
- 1.4 INSULATION RESISTANCE: 1000MΩ MIN. AT 500V DC.
- 1.5 WITHSTAND VOLTAGE:1000V D.C. or A.C. PEAK;ONE CONTACT TO ALL OTHER CONTACTS CONNECTED TOGETHER, 1500V D.C. OR A.C. PEAK;ALL CONTACTS CONNECTED TOGETHER TO SHIELD, (HOUSING/MOUNTING PLATE) IF PRESENT. @ 0.5mA 50 Hz OR 60 Hz A MINUTE

2. MECHANICAL:

- 2.1 RETENTION STRENGTH:50N MIN. FOR 60S±5S
- 2.2 OPERATING LIFE:750 CYCLES.
- 2.3 INSERTION FORCE:30N MAX.

3. ENVIRONMENTAL:

- 3.1 OPERATION: -25°C~+55°C GB 10753-89
- 3.2 STORAGE: -10°C~+40°C RELATIVE HUMIDITY<80%, GB 10753-89
- 3.3 STORAGE TIME:12 MONTHS
- 3.4 SALT SPRAY TEST:SEE TABLE

4. CHARACTERISTICS:

- 4.1 PLUG WILL ACCEPT 24 OR 26 AWG STRANDED WIRE HAVING A MAXIMUM INSULATION DIAMETER OF 0.89-0.99 MM AND A MAXIMUM DIAMETER CABLE JACKET OF 5.40 MM

