



SPECIFICATION:

CONTACT RATING: 6A 250VAC, 10A 125VAC

INSULATION RESISTANCE: 500V d.c. for 1 min.

ELECTRIC STRENGTH: 2000V a.c. for 1 min.

NO	DESCRIPTION	MATERIAL	QTY	SGS REPORT NO.
1	PIN	BRONZE, NICKEL	2	CE/2006/65586
2	HOUSING	ABS 777B,	1	CE/2006/13027
3	GROUND	ABS 777B,	1	CE/2006/13027
4	CONTACT	C2680 BRONZE, NICKEL	2	CE/2006/65586

Cr+6 < 1000ppm
 Cd < 100ppm
 Hg < 1000ppm
 Pb < 1000ppm
 PBBs < 1000ppm
 PBBEs < 1000ppm

TOLERANCES
0.5MM-5MM=±0.2MM
5MM-30MM=±0.4MM
30MM-120MM=±0.6MM
120MM-315MM=±1.0MM
315MM-1000MM=±1.6MM
1000MM-2000MM=±2.4MM

97.1128	更正尺寸	核准日期 Date	設計 Designed By	比例尺 Scale
95.7.28	UPDATE 報告	28 NOV 2008	C.J HUANG	1:1
94.2.22	增加規格說明	核准 Approved By	繪圖 Drew By	單位 UNIT
修正日期	修正說明	J.F. WANG	C.T WANG	m/m



AC-7210
 AUSTRALIAN TYPE
 ADAPTOR PLUG,6A 250V

REF. NO.