



TOP Electronic Components S.A.

66 ALKMINIS & ARISTOVOULOY St.,
118 53 K. PETRALONA,
ATHENS, GREECE.

Tel : +30-210-3428690

Fax : +30-210-3428692

Email : info@topelcom.gr

VAT. Number : 094356121

RG6/U (UL) Specifications

Characteristics

Impedance: 75+/-3 Ohm

Velocity of Propagation: 85%

Return Loss: >=20dB

Description:

Construction

Center Conductor: 1.02mm Copper Clad Steel (+/-0.2mm)

Dielectric: 4.57mm Foam PE (+/-0.2mm)

Shield: Aluminum Foil

Braid Coverage: 0.12/64 @ 45%-60% Aluminum braid

Jacket: 6.80mm (+/-0.2mm) UL approved PVC

Characteristics

Impedance: 75+/-3 Ohm

Velocity of Propagation: 85%

Return Loss: >=20dB

Attenuation[@ 68F. (20.)]

5MHz	2.2dB
55MHz	5.5dB
211MHz	10.3dB
270MHz	11.3dB
300MHz	11.9dB
330MHz	12.6dB
400MHz	13.9dB
450MHz	14.7dB
550MHz	16.5dB
750MHz	19.3dB
870MHz	20.9dB
1000MHz	22.5dB