

TECHNICAL DATA SHEET

Product Code: Shielded Alarm Cable 10X0.22 LSOH

Part Number: 02.006.0188

Page: 1 of 1

Date: 2022-05-18

	Dimensional Features	Material Breakdown
Inner Conductor	7/0.20CCA(+0.005/-0.005)mm	Forged Copper Clad Aluminum
Insulation	1.0(+/-0.10)mm	Red, Black, Blue, Yellow, Green, White, Brown, Orange Grev. Pink LSOH insulation
Assembly	Non	Non
Drain wire	7/0.20CCA(+0.005/-0.005)mm	Forged Copper Clad Aluminum
Shielding	18.00(+/-0.10)mm	Overall Aluminium/Polyester foil (uncoloured)
Ripcord	200D×3	White synthetical fibres
Sheath	5.10(+/-0.20)mm	White LSOH Sheath RAL9003

▪ Electrical Characteristics

Max. Conductor (A) DC Resistance at 20°C(Ω/100M) <12.5

Min. Insulation DC Resistance at 20°C(MΩ*M) >200

Rated Temperature(°C) 90°C

Rated Voltage(V) 300V

▪ Physical Characteristics


Minimum Bending Radius(mm) 15×D

Conductor Elongation at Break(%) >5%

Sheath Tensile Strength (N/mm²) 10.0

Sheath Elongation at Break(%) 125.0%

▪ Cable Construction



Remark: Please contact us if you have more requirements or specifications subject to change, or else in accordance with the standards.

Please note that the above specification is based on the received requirements and/or our design, we reserve the right to update it to reflect the latest changes

TOP Electronic Components S.A.

66, Alkminis Str., Athens 118 53

Tel: +30-210-3428690/693 ext. #217 Fax: +30-210-3428692