



- Operating Temperature: -40~ +140
- Insert: Brass. Steel with Zncoating
- Material: BMC (Bough Moulding Compound)
SMC(Sheet Moulding Compound)
- Colour, Insert,material In capability accordance screw with customer needs

SM BUS BAR INSULATOR(Drum)




SM-20 (mm)

Tensile strength(LBS)	300
Voltage withstand(KV)	5
Torgue strength(FTLBS)	4
screw(mm)	5
screw depth(mm)	7




SM-45 (mm)

Tensile strength(LBS)	1000
Voltage withstand(KV)	14
Torgue strength(FTLBS)	20
screw(mm)	8
screw depth(mm)	11




SM-25 (mm)

Tensile strength(LBS)	500
Voltage withstand(KV)	6
Torgue strength(FTLBS)	6
screw(mm)	6
screw depth(mm)	9




SM-51 (mm)

Tensile strength(LBS)	1000
Voltage withstand(KV)	15
Torgue strength(FTLBS)	20
screw(mm)	8
screw depth(mm)	14




SM-30 (mm)

Tensile strength(LBS)	550
Voltage withstand(KV)	8
Torgue strength(FTLBS)	8
screw(mm)	8
screw depth(mm)	11




SM-60 (mm)

Tensile strength(LBS)	1200
Voltage withstand(KV)	20
Torgue strength(FTLBS)	35
screw(mm)	10
screw depth(mm)	15




SM-35 (mm)

Tensile strength(LBS)	600
Voltage withstand(KV)	10
Torgue strength(FTLBS)	10
screw(mm)	8
screw depth(mm)	11




SM-76 (mm)

Tensile strength(LBS)	1500
Voltage withstand(KV)	25
Torgue strength(FTLBS)	40
screw(mm)	10
screw depth(mm)	20



SM-40 (mm)

Tensile strength(LBS)	650
Voltage withstand(KV)	12
Torgue strength(FTLBS)	12
screw(mm)	8
screw depth(mm)	11



SM-80 (mm)

Tensile strength(LBS)	
Voltage withstand(KV)	
Torgue strength(FTLBS)	
screw(mm)	
screw depth(mm)	