

PIN OUT

CN1 (568B)	CN2 (568B)
WHITE/ORANGE 1	1 WHITE/ORANGE
ORANGE 2	2 ORANGE
WHITE/GREEN 3	3 WHITE/GREEN
GREEN 6	6 GREEN
BLUE 4	4 BLUE
WHITE/BLUE 5	5 WHITE/BLUE
WHITE/BROWN 7	7 WHITE/BROWN
BROWN 8	8 BROWN

NOTE:


1. Electrical test:

(1). 100% open short & miss wire test;

(2). Insulation resistance: DC 300V 10M Ω ;(3). Contactor resistance: 3 Ω ;

2. RoHS compliant

MATERIAL LIST:

DRAW NO.				PRODUCT NAME		CAT.6 UTP 8P8C - 8P8C		
①	CABLE	Cat.6 7/0.16CCA*4P UTP JACKET:PVC OD:5.7 \pm 0.1mm	1	CUSTOMER	VIEW	Tolerance		
②	PVC	75A PVC	2	ITEM NO.		X.	\pm 1.00	
③	8P8C PLUG	RJ45 8P8C PLUG, CAT.6 UTP Pin GOLD 3U", Circle Type. Take 6 under 2 stent	2	APPOBY	CHECKBY	DRAWNBY	UNTT	MM
NO.	PARTS NAME	SPECIFICATION DESCRIPTION	QT'Y	REMARK			Page	1 of 1