

## PIN OUT

| CN1 (568B)     | CN2 (568B)     |
|----------------|----------------|
| WHITE/ORANGE 1 | 1 WHITE/ORANGE |
| ORANGE 2       | 2 ORANGE       |
| WHITE/GREEN 3  | 3 WHITE/GREEN  |
| GREEN 6        | 6 GREEN        |
| BLUE 4         | 4 BLUE         |
| WHITE/BLUE 5   | 5 WHITE/BLUE   |
| WHITE/BROWN 7  | 7 WHITE/BROWN  |
| BROWN 8        | 8 BROWN        |

## NOTE:


1. Electrical test:

(1). 100% open short &amp; miss wire test;

(2). Insulation resistance: DC 300V 3M $\Omega$ ;(3). Contactor resistance: 3 $\Omega$ ;

2. RoHS compliant

## MATERIAL LIST:

|     |            |  |      | DRAW NO. | PRODUCT NAME  | CAT. 5E UTP 8P8C - 8P8C                         |      |             |
|-----|------------|--|------|----------|---|---|------|-------------|
| ①   | CABLE      | Cat. 5e 7/0.16CU*4P UTP JACKET:PVC OD:5.0 $\pm$ 0.2mm  | 1    | CUSTOMER | VIEW  | Tolerance<br>X. X $\pm$ 1.00<br>X. X $\pm$ 0.50 |      |             |
| ②   | PVC        | 75A PVC  | 2    | ITEM NO. |  |   |      |             |
| ③   | 8P8C PLUG  | RJ45 8P8C PLUG, CAT. 5e UTP Pin GOLD 3U", Circle Type. | 2    | APPOBY   | CHECKBY   | DRAWNBY   | UNTT | MM          |
| NO. | PARTS NAME | SPECIFICATION DESCRIPTION                              | QT'Y | REMARK   |   |   |      | Page 1 of 1 |