

# 503 Si

Connection:	conductor size 0.5 - 2.5 mm <sup>2</sup> (with wire protector) conductor size 0.5 - 6.0 mm <sup>2</sup> (without wire protector)
Fixing:	by screw or rivet size Ø 3.1 mm (1 pole Ø 2.1 mm) and anti-twist protection
Torque screw:	M3: $\cup$ max. 0.5 Nm
Stripping length:	7 - 7.5 mm
Fuse size:	5 x 20 mm, power dissipation 2.5 W at T 23 °C
Important approvals:	VDE, UL
Accessories:	covers (page 85), strain reliefs (page 86)
Upon request:	marking labels, pre-assembled fuses, printing, different polyamides (in particular glow wire to EN 60335-1), different screws

Description	Item	Order Number	PU
<b>with Wire Protectors</b>			
1 pole	503 Si/ 1 DS	170301	100
2 pole	503 Si/ 2 DS	170302	300
3 pole	503 Si/ 3 DS	170303	200
4 pole	503 Si/ 4 DS	170304	200
5 pole	503 Si/ 5 DS	170305	100
<b>without Wire Protectors</b>			
1 pole	503 Si/ 1	170201	100
2 pole	503 Si/ 2	170202	300
3 pole	503 Si/ 3	170203	200
4 pole	503 Si/ 4	170204	200
5 pole	503 Si/ 5	170205	100

