



REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	LJH 09/25/05*		LJC 09/25/05*
B	在端子间距更改由.6更改为0.8	LL 11/29/06*		

NOTES:



- ELECTRICAL CHARACTERISTICS:
 - 1.1 CONTACT RESISTANCE: 30mΩ Max. INITIAL.
 - 1.2 DIELECTRIC WITHSTANDING VOLTAGE: 500V AC(rms) FOR 1 MINUTE.
 - 1.3 INSULATION RESISTANCE: 1000MΩ Min.
- ENVIRONMENT CHARACTERISTICS:
 - 2.1 OPERATING TEMPERATURE: 0°C~+85°C.
 - 2.2 STORAGE TEMPERATURE: -20°C~+70°C.
- PRODUCT NUMBER CODE:

DS1024- X X X


- CONTACT PLATING
- F1: FULL GOLD PLASH
- O: SELECTIVE GOLD FLASH
- MOUNTING TYPE
- R: R/A TYPE
- No. OF CONTACTS
- 1*1-1*40
- 2*2-2*40



SINGLE ROW
N:NUMBER OF CONTACTS



DUAL ROWS
N:NUMBER OF CONTACTS/2



GENERAL TOLERANCE		ANGLE TOLERANCE	
X	±0.60	X	±5°
.X	±0.38	.X	±3°
.XX	±0.25	.XX	±2°

PROJECTION		TITLE
UNITS	mm	FEMALE HEADER PITCH 2.54MM R/A TYPE
SHEET SIZE	A4	SERIES DS1024 SERIES

2	CONTACT	COPPER ALLOY	GOLD PLATED	DRAWING TYPE	CUSTOMER
1	HOUSING	THERMOPLASTIC	UL 94 V-0	SCALE	1:1 SHEET 1 OF 1
ITEM	PART NAME	PART NO.	MATERIALS	FINISHED	DRAWING NO. C-DS1024-XXXX