


VGA Cable 3 + 4

Item No:PL-VG152 AM-AM

Item No:PL-VG156 AM-AF



FEATURES:

VGA cable is with a three-row 15-pin DE-15 connector, It used to connect and send signals between computers and monitors, Television, Laptop, Projector and so on. It Can support various VGA resolutions, ranging from 320×400px @70 Hz / 320×480px @60 Hz (12.6 MHz of signal bandwidth) to 1280×1024px (SXGA) @85 Hz (160 MHz) and up to 1920×1080px

SPECIFICATIONS:

Version	VGA 3 + 4
Connector Type	15PIN Male to Male; Male to Female
Conductor	Main core: Copper
Conductor Gauge:	30AWG~24AWG
Connector Plating	Nickel -plated
Shielding	Aluminum Foil + Braiding
Drain Wire.:	CCA
Outer Jacket OD.:	7.0~8.0mm
Outer Jacket Material:	PVC
Color:	Beige
Length:	1.5m~30m
Packing:	Polybag&Color box

Electrical Specification:

Conductor Resistance:	@20°C Max. 30AWG:376.96Ω/Km
Normal Impedance with Tolerance	75±5Ω
Normal Capacitance:	58PF/M
Maximum Resolution Supported:	1920*1080px
Insulation Resistance:	10MΩ·KM min at 20°C DC 500V
Dielectric Strength:	AC 500V/1 Minute

Physical Characteristics:

- ◆Voltage Rating : 30V
- ◆Minimum Bend Radius:85mm
- ◆Contact Resistance:2 Ohm max
- ◆Working Temperature:-25°C~80°C